


# INTERIOR ACOUSTICS FRONTIER





**FRONTIER™**  
**ACOUSTIC FINS**  
DESIGN: TUNDRA  
COLOUR: FLATIRON

# FRONTIER™

## ACOUSTIC CEILING AND WALL SYSTEM

### BE MORE ATTUNED TO YOUR SPACE

Frontier™ offers targeted sound absorption, endless configurations, and stress-free installation without compromising acoustic performance.

Frontier is an innovative acoustic system designed for targeted sound absorption for today's ever-changing open-plan workspaces, retail, education and hospitality applications. Formed by just three elements including Autex Mounting Clips, Autex Frontier Extrusions, and Acoustic Fins or Rafts, Frontier allows designers to mix and match colours and styles, create endless configurations, and enjoy quick and stress-free installations.

Whether specifying Fin or Raft styles, Frontier offers incredible acoustic performance that can be 'tuned' for the space. Multiuse aluminium channels and clips allow for adjustment on-site, further enhancing the surrounding environment.




# FRONTIER™

## FEATURES AND BENEFITS

- Choose from 17 colours and nine styles, including Fins or Raft for a bold, dimensional statement.
- Create a more comfortable and personalised experience by tuning the acoustic effect. Simply move the Fins or Rafts closer together or further apart.
- Mount Fins or Rafts flush to the ceiling to 'blend in', fix them to rails or suspend them using extension rods.
- Frontier can be configured to fit the space perfectly.

Fins and Rafts are made with our high-performing, highly-compressed polyester material, which uses advanced fibre locking technology, instead of adhesives or other materials which can be harmful to the environment.




**FRONTIER™**  
**ACOUSTIC FINS**  
DESIGN: CUSTOM  
COLOUR: SAVOYE



# FRONTIER™

## THE SYSTEM

Increase productivity on-site, saving installation time and material costs.




### AUTEX FRONTIER EXTRUSIONS

Multiuse aluminium channels along with a system of components, act as a support for Acoustic Fins or Rafts and allow easy installation and adjustments on site.




### AUTEX MOUNTING CLIPS

The exclusive Frontier connector clip 'clicks' in place to enable Fins or Rafts to be attached directly to the ceiling channel, leaving no exposed fasteners or adhesives.




### CHOOSE ACOUSTIC FIN OR RAFT STYLES

Enjoy the freedom to create new and interesting ceiling and wall features with Fins or Rafts. Choose Fins for simple and stylish arrangements, or Rafts to add dimensional shape and volume.




### ARRANGEMENT VERSATILITY

Arrange and space out Fins or Rafts in countless configurations. Install in standard or custom sequences, or bring your vision to life working side-by-side with Autex in-house acoustic design experts and account managers.



### EASY ASSEMBLY

Frontier goes together quickly and efficiently, saving time on site. Dismantle or remove the system from its setting and reassemble or reposition just as easily and quickly.



### EVEN EASIER TO DISASSEMBLE


Frontier uses no adhesives. Each component can be removed quickly at the end of life, minimising negative impacts on the environment at the time of disposal.




# FRONTIER™

## SYSTEM COMPONENTS


### PACK COMPONENTS




**RAFNEX**  
Frontier 12mm Extrusion




**RAFNEX24**  
Frontier 24mm Extrusion



**RAFNEXRT**  
Frontier Raft Extrusion




**RAFTCC**  
Autex Mounting Clip




**RAFCCT**  
Autex Frontier Channel Connector


### ACCESSORIES




**RAFWCP**  
Autex Removable VV-Clip




**RAFHDCC**  
Autex Heavy Duty Frontier Channel  
Connector with 4x M5 Grub Screws




**RAFM6GC**  
Velda Grid Connector with M6 Thread



**RAFM6MP**  
Velda Magnet Pot with M6 Thread  
and Cable Adaptor



**RAHVAS**  
Autex Adjustable Suspension Set - Channel



**FRONTIER™**  
**ACOUSTIC FINS**  
DESIGN: CUSTOM AXIS  
COLOUR: FLATIRON



 **FRONTIER™**  
**ACOUSTIC RAFT**  
DESIGN: BEAM 100  
COLOUR: PETRONAS

# FRONTIER™

## ACOUSTIC RAFT

Raft brings an innovative, bold new dimension to our Frontier range. Available in four unique designs, Raft is scored, folded and 'zipped' together using a locking channel. Now you can arrange and space Raft in countless configurations, without loss of acoustic performance.


Enjoy the freedom to create bold new designs using standard packs, or customise the system to match the scale of the space.



# FRONTIER™ ACOUSTIC RAFT

## FEATURES AND BENEFITS

- Delivers a solid appearance, yet, due to its scored and layered construction, each style is hollow and lightweight.
- Made from highly-absorbent, compressed material, Rafts hold their shape. They won't bend or warp after installation.
- Create long and linear ceiling features with quick, secure joins. Remove the weight and tasks related to finishing elements that would occur with solid wood or steel beams.
- Adjust on-site, allowing for targeted sound absorption and personalisation of the space.
- Disassemble quickly and remove at the end of life.







# FRONTIER™ ACOUSTIC RAFT

## APPLICATIONS

- Suitable for a variety of spaces, including offices, education, retail, hospitality and commercial interior applications.
- Can be installed either fixed or suspended from ceilings or mounted to walls.

## SPECIFICATION

Acoustic absorber Frontier Acoustic Raft (Blade: 2400 x 257 x 70), (Beam 100: 2400 x 92 x 70mm), (Beam 250: 2400 x 232 x 70 mm), (Trapezoid: 2400x 160 x225mm), Colour ( ),

Fire Rating ISO 9705: 1993: Group 1-S,

AS ISO 9705 – 2003: Group 1,

EN13501-1: 20074A1: 2009: B-s2,d2

ASTM E-84-15a: Class A, FS:0 - SD:45.


Seismic bracing as per local building code requirements.

Supplied with Autex suspension kits for suspension or Frontier™ clips for direct fixing, fix with countersunk fastener appropriate for the substrate. Install as per Frontier Install Instructions.



# FRONTIER™

## ACOUSTIC RAFT DESIGNS




**DESIGN** BLADE **COLOUR** LOTUS - SEE PAGE 39 FOR FULL COLOUR RANGE

\*Images as shown are with 2 packs.

# FRONTIER™

## ACOUSTIC RAFT DESIGNS





**DESIGN** TRAPEZOID **COLOUR** GALAXY - SEE PAGE 39 FOR FULL COLOUR RANGE

\*Images as shown are with 2 packs.

# FRONTIER™

## ACOUSTIC RAFT DESIGNS




**DESIGN BEAM 250 COLOUR FALLING WATER** - SEE PAGE 39 FOR FULL COLOUR RANGE

\*Images as shown are with 2 packs.

# FRONTIER™

## ACOUSTIC RAFT DESIGNS



**DESIGN BEAM 100 COLOUR OPERA** - SEE PAGE 39 FOR FULL COLOUR RANGE

\*Images as shown are with 2 packs.





ABSORPTION COEFFICIENT ACCORDING TO ISO 354




Table presents the practical sound absorption coefficients as according to ISO 11654. Graph presents third octave sound absorption coefficients (According to ISO 354 Measurement of sound absorption in a reverberation room.) The NRC rating is determined as the arithmetic average of the absorption coefficients measured by one-third octave bands centred on 250 Hz, 500 Hz, 1000 Hz and 2000 Hz. and rounded to the nearest 0.05.

DESCRIPTION	University of Auckland Test report number	FREQUENCY (Hz)						
		125	250	500	1000	2000	4000	NRC
Frontier™ Raft 12mm Trapezoid, 200mm off ceiling @ 300mm centres	T1905-11	0.25	0.65	0.85	1.05	1.15	1.15	0.95
Frontier™ Raft 12mm Blade, 200mm off ceiling @ 300mm centres	T1905-10	0.20	0.35	0.60	1.00	1.25	1.25	0.80
Frontier™ Raft 12mm Beam 100, 200mm off ceiling @ 150mm centres	T1945-4	0.05	0.25	0.55	0.95	1.15	1.20	0.75
Frontier™ Raft 12mm Beam 250, 200mm off ceiling @ 300mm centres	T1945-5	0.20	0.45	0.70	1.10	1.35	1.30	0.90

PRODUCT SPECIFICATIONS

Product Name	Frontier™ Acoustic Raft
Composition	100% Polyester Fibre (PET) Channel: Aluminium
Fin Length	2400mm
Tolerance	(+/-0.5mm)
Thickness	12mm
Tolerance	(+/-6%)
Weight	2300gsm

INSTALLATION

Install as per Autex recommendations.  
Install instructions are included in each pack or available on the website.

ACOUSTIC PERFORMANCE

Frontier Acoustic Raft is specifically designed to reduce and control reverberated noise (echo) in building interiors.



**LIGHT REFLECTANCE VALUES BY COLOUR**

Pavilion	78	Zenith	22
Opera	49	Lotus	16
Savoye	47	Galaxy	16
Senado	45	Iron Bank	13
Rosada	45	Pinnacle	8
Acros	42	Empire	6
Falling Water	36	Tree House	3
Bosco	29	Petronas	2
Flatiron	25		

MEASURED IN ACCORDANCE WITH BS 8493:2008+A1:2010

**FIRE RATING**

Frontier™ is a value-added product made from Autex Cube™ as the base material. Cube™ has been evaluated using the following test methods:

**ISO 9705: 1993**

Classification: Group 1-S  
 Smoke Production Rate: <5.0m²/s

As required by NZBC C/VM2

**AS ISO 9705 - 2003**

Classification: Group 1  
 (SMOGRArc): <100m²/s²  
 Assessed using methodology AS ISO 9705:2003 in accordance with AS 5637.1:2015, as required by BCA Specification C1.10-4 FI 4974 dated 16<sup>th</sup> September, 2012 and FAR 4055-3 dated 31<sup>st</sup> July, 2019

**EN13501-1:2007+A1:2009**

B - s2, d2  
 VF336911 dated 25th February 2014

**ASTM E-84-15a**

Class A, FS:0 - SD:45  
 RJ4479-2 dated 25th January, 2016

**VOC EMISSIONS**

Autex polyester has been tested for chemical emmissions (Report: CV170908) and is classified as low VOC. VOC concentration: 0.009 mg/m3 (7 days)

**WATER VAPOUR SORPTION**

ASTM C1104 / C1104M-13a  
 Test conditions: 49°C, 95%RH  
 Water vapour absorbed and adsorped after 4 days: 0.4% by weight

**MICROBIAL RESISTANCE**

ASTM G21-15  
 Growth Rating: 0 (No growth)  
 Frontier Acoustic Raft does not promote the growth of moulds and mildew.

**FABRIC CARE**

Blot spills from fabric quickly. Wipe with a damp cloth. Avoid rubbing and excessive amounts of water as this will affect the finish. Use carpet or upholstery shampoo as directed. Blot with a clean dry cloth after each application of solution.

Custom printed Cube™ requires the services of a specialist cleaning company. Refer to the Frontier Acoustic Raft Cleaning and Maintenance Guide for more information.

**ENVIRONMENTAL**

Autex is committed to best practice through our ISO 9001 and ISO 14001 certified Quality and Environmental Management Systems.

Autex Frontier Raft contains a minimum of 45% previously recycled polyester fibre (from PET bottle-flake). Off-cuts and manufacturing waste are re-used or recycled wherever possible.

Autex Frontier Acoustic Raft is manufactured from 100% polyester fibres and does not contain formaldehyde binders. Autex polyester fibres support safer indoor air quality and will not become a potential airborne pollutant.

**SERVICE**

For further information about Frontier Acoustic Raft, Autex Cube™ or any other Autex product, please contact your Autex account manager or visit our website.







# FRONTIER<sup>TM</sup>

## ACOUSTIC FINS


Frontier Acoustic Fins create design freedom and flexibility using simple but stylish arrangements. Fins are available in five standard designs in 12mm and 24mm thicknesses. Customise to create engaging and unique patterns and sequences of your own.



# FRONTIER™ ACOUSTIC FINS

## FEATURES AND BENEFITS

- Delivers excellent acoustic performance
- Suitable for wall and ceiling applications
- Supplied in kits including acoustic fins and fixing hardware
- Can be subtle or a feature design for small or large spaces
- Low VOC – beneficial for IEQ
- Not made from fibreglass or mineral fibre and does not contain formaldehyde, crystalline silica or other carcinogens, common to traditional fibrous absorbers
- Cleanable and easily demountable
- Includes high recycled content and designed for disassembly
- Highly durable so you're assured of long-term stability and performance







# FRONTIER™ ACOUSTIC FINS

## APPLICATIONS

- Suitable for offices, education, retail, hospitality and commercial interiors
- Fix or suspend acoustic ceiling and wall system
- Creates breakout zones in large open plan areas
- Hides ceiling services

## SPECIFICATION


Acoustic absorption system shall be Frontier ( ) as compiled by Autex [www.autexindustries.com](http://www.autexindustries.com)

Acoustic absorber Frontier™ Acoustic Fins (2400/custom) mm length x (300mm nominal / Axis 150mm) depth x (12/24)mm gauge, spaced at ( )mm centres. Colour ( ), sound absorption: 100/200mm centres Class B, 300mm centres Class C, Fire Rating ISO 9705: 1993: Group 1-S, AS ISO 9705 – 2003: Group 1, EN13501-1:2007+A1:2009: B - s2, d2, ASTM E-84-15a -12mm: Class A, FS:0 - SD:45.


Supplied with Frontier Connector Clips, Frontier Channel, Frontier Fins. Fix with 6g countersink fastener appropriate for the substrate. Install as per Frontier Install Instructions.

# FRONTIER™

## ACOUSTIC FIN DESIGNS



**DESIGN TUNDRA COLOUR GALAXY** - SEE PAGE 39 FOR FULL COLOUR RANGE



**DESIGN DUNE COLOUR FALLING WATER** - SEE PAGE 39 FOR FULL COLOUR RANGE


\*Images as shown are with 2 packs.

# FRONTIER™

## ACOUSTIC FIN DESIGNS



**DESIGN SIERRA COLOUR LOTUS** - SEE PAGE 39 FOR FULL COLOUR RANGE




**DESIGN TALUS COLOUR ACROS** - SEE PAGE 39 FOR FULL COLOUR RANGE

\*Images as shown are with 2 packs.




# FRONTIER™

## ACOUSTIC FIN DESIGNS



**DESIGN** AXIS (12MM ONLY) **COLOUR** SAVOYE - SEE PAGE 39 FOR FULL COLOUR RANGE

\*Images as shown are with 2 packs.



**FRONTIER™**  
**ACOUSTIC FINS**  
DESIGN: CUSTOM AXIS  
COLOUR: EMPIRE





**FRONTIER™  
ACOUSTIC FINS**  
DESIGN: TALUS  
COLOUR: SENADO, ACROS  
AND FALLING WATER

### ABSORPTION COEFFICIENT ACCORDING TO ISO 354




Table presents the practical sound absorption coefficients as according to ISO 11654. Graph presents third octave sound absorption coefficients (According to ISO 354 Measurement of sound absorption in a reverberation room.) The NRC rating is determined as the arithmetic average of the absorption coefficients measured by one-third octave bands centred on 250 Hz, 500 Hz, 1000 Hz and 2000 Hz. and rounded to the nearest 0.05.

DESCRIPTION	University of Auckland Test report number	FREQUENCY (Hz)						
		125	250	500	1000	2000	4000	NRC
Frontier™ Axis 12mm 150mm deep 300mm centres	T1525-11	0.20	0.50	0.75	0.65	0.90	1.05	0.70
Frontier™ 12mm 300mm deep 100mm centres	T1525-18	0.30	0.65	0.80	1.20	1.45	1.60	1.00
Frontier™ 12mm 300mm deep 200mm centres	T1525-16	0.30	0.60	0.70	1.00	1.30	1.50	0.90
Frontier™ 12mm 300mm deep 300mm centres	T1525-17	0.25	0.50	0.60	0.80	1.10	1.25	0.75

### PRODUCT SPECIFICATIONS

Product Name	Frontier™ Acoustic Fins
Composition	Fin: 100% Polyester Fibre (PET) Aluminium Channel
Dimensions	Fin Length: 2400mm
Tolerance	(+0.5mm)
Thickness	12mm
Tolerance	(+/-6%)
Weight	2300 gsm

### ACOUSTIC PERFORMANCE

Frontier is specifically designed to reduce and control reverberated noise (echo) in building interiors.

### INSTALLATION

Install as per Autex recommendations.  
Install instructions are included in each pack or available on the website.



**ABSORPTION COEFFICIENT ACCORDING TO ISO 354**




Table presents the practical sound absorption coefficients as according to ISO 11654. Graph presents third octave sound absorption coefficients (According to ISO 354 Measurement of sound absorption in a reverberation room.) The NRC rating is determined as the arithmetic average of the absorption coefficients measured by one-third octave bands centred on 250 Hz, 500 Hz, 1000 Hz and 2000 Hz, and rounded to the nearest 0.05.

DESCRIPTION	University of Auckland Test report number	FREQUENCY (Hz)						
		125	250	500	1000	2000	4000	NRC
Frontier™ 24mm 300mm deep 100mm centres	T1812-4	0.35	0.70	0.95	1.25	1.35	1.30	1.05
Frontier™ 24mm 300mm deep 200mm centres	T1812-5	0.25	0.55	0.70	1.10	1.30	1.30	0.90
Frontier™ 24mm 300mm deep 300mm centres	T1812-6	0.20	0.45	0.60	1.00	1.25	1.20	0.85

**PRODUCT SPECIFICATIONS**

Product Name	Frontier™ Acoustic Fins
Composition	Fin: 100% Polyester Fibre (PET) Aluminium Channel
Fin Length	2400mm
Tolerance	(+/-0.5mm)
Thickness	24mm
Tolerance	(+/-6%)
Weight	4600 gsm

**ACOUSTIC PERFORMANCE**

Frontier is specifically designed to reduce and control reverberated noise (echo) in building interiors.

**INSTALLATION**

Install as per Autex recommendations.  
Install instructions are included in each pack or available on the website.



**LIGHT REFLECTANCE VALUES BY COLOUR**

Pavilion	78
Opera	49
Savoye	47
Senado	45
Rosada	45
Acros	42
Falling Water	36
Bosco	29
Flatiron	25

MEASURED IN ACCORDANCE WITH BS 8493:2008+A1:2010

**FIRE RATING**

Frontier™ is a value-added product made from Autex Cube™ as the base material. Cube™ has been evaluated using the following test methods:

**ISO 9705: 1993**

Classification: Group 1-S  
 Smoke Production Rate: <5.0m²/s  
 As required by NZBC C/VM2

**AS ISO 9705 - 2003**

Classification: Group 1  
 (SMOGRArc): <100m²/s²  
 Assessed using methodology AS ISO 9705:2003 in accordance with AS 5637.1:2015, as required by BCA Specification C1.10-4 FI 4974 dated 16<sup>th</sup> September, 2012 and FAR 4055-3 dated 31<sup>st</sup> July, 2019

**BS EN 13501-1:2018**

Wall applications  
 Classification: B-s2,d0 (Cube™ 12mm)  
 Tested using BS EN ISO 11925-2:2020 and BS EN 13823:2020 and classified in accordance with BS EN 13501-1:2018, as required by BS EN 15102:2007 + A1:2011.EUI-20-000268-A

Ceiling applications  
 Classification: B-s2,d0 (Cube™ 12mm)  
 Tested using BS EN ISO 11925-2:2020 and BS EN 13823:2020 and classified in accordance with BS EN 13501-1:2018, as required by BS EN 13964:2014.EUI-20-000268-B

**ASTM E-84-15a**

Class A, FS:0 - SD:45 (Cube™ 1/2")  
 RJ4479-2 dated 25th January, 2016  
 Class A, FS:0 - SD:65 (Cube™ 1")  
 RJ4479-1 dated 25th January, 2016

**VOC EMISSIONS**

Autex polyester has been tested for chemical emissions in accordance with ASTM D5116 and is considered as a low VOC product.  
 VOC concentration: 0.009 mg/m³ (7 days).

**WATER VAPOUR SORPTION**

ASTM C1104 / C1104M-13a  
 Test conditions: 49°C, 95%RH  
 Water vapour absorbed and adsorped after 4 days: 0.4% by weight.

**MICROBIAL RESISTANCE**

ASTM G21-15  
 Growth Rating: 0 (No growth)  
 Frontier™ does not promote the growth of mould and mildew.

Zenith	22
Lotus	16
Galaxy	16
Iron Bank	13
Pinnacle	8
Empire	6
Tree House	3
Petronas	2

**COLOUR FASTNESS TO LIGHT**

Frontier™ is suitable for indoor use only.  
 Light fastness is dependent on use and exposure.  
 Frontier has been evaluated to the following standard:  
 ISO 105-B02:2014  
 Rating: 6 (Highest = 7)

**COLOUR FASTNESS TO RUBBING**

ISO 105-X12:2016  
 Dry Rating: 4-5 (Highest = 5)  
 Wet Rating: 4-5 (Highest = 5)

**PATTERN REPEAT**

Non-woven. No pattern repeat but product has directional grain. Product may vary from samples and batch to batch due to fibre blending and lay-up which is an inherent feature of this product.

**FABRIC CARE**

Blot spills from fabric quickly. Wipe with a damp cloth. Avoid rubbing and excessive amounts of water as this will affect the finish. Use carpet or upholstery shampoo as directed. Blot with a clean dry cloth after each application of solution.

Custom printed Cube require the services of a specialist cleaning company. Refer to the Frontier Cleaning and Maintenance Guide for more information.

**ENVIRONMENTAL**

Autex is committed to best practice through our ISO 9001 and ISO 14001 certified Quality and Environmental Management Systems.

Autex Frontier™ contains a minimum of 45% recycled polyester fibre (from PET bottle-flake). Off-cuts and manufacturing waste is re-used or recycled wherever possible.

Autex Frontier™ is manufactured from 100% polyester fibres and do not contain formaldehyde binders. Autex polyester fibres support safer indoor air quality and will not become a potential airborne pollutant.

**SERVICE**

For further information about Frontier™, Autex Cube™ or any other product, please contact your Autex account manager or visit our website.

FRONTIER™  
 COLOUR OPTIONS





# FRONTIER<sup>TM</sup> CUSTOMISATION

We know that no two projects are exactly the same, so why should the products or services going into them be? This is why we are proud of our ability to customise any of our products to suit your needs.

Being manufacturers, engineers and creatives, we have the capacity to transform, cut, mould, or build our products to create acoustic solutions truly unique to you and your space.

If you have an idea, let's work together to make it happen. If you want to customise Frontier<sup>TM</sup> for your next project, get in touch with your Autex account manager or visit our website [www.autexindustries.com/contact-us](http://www.autexindustries.com/contact-us)







## CARING FOR THE ENVIRONMENT

Frontier™ is manufactured using 100% polyester fibre and contains a minimum of 45% previously recycled fibre (from PET plastics). Many of our products are designed to be recycled at the end of their life too.

We use Life Cycle Analysis (LCA) to understand the environmental impacts of our products and set targets to reduce these. All our products have been verified as low VOC and are free from chemical binders making them great for indoor environmental quality (IEQ). We have continual improvement programmes in which we implement a range of initiatives to mitigate the environmental 'hotspots' that we have identified. Our products are GreenRate Level A, LCARate Gold and PHD level platinum certified.

Frontier™ is made from Cube™ which is Declare certified to be Red List free and can be used in Living Building Challenge projects. Autex has a high functioning Environmental Management System (ISO 14001) to enhance our environmental performance and contribute to sustainable development.



**Declare.**



**whiteboards  
and pinboards**

1300 344 978  
Sales@whiteboardsandpinboards.com.au  
www.whiteboardsandpinboards.com.au





whiteboards  
and pinboards



1300 344 978



[Sales@whiteboardsandpinboards.com.au](mailto:Sales@whiteboardsandpinboards.com.au)



[www.whiteboardsandpinboards.com.au](http://www.whiteboardsandpinboards.com.au)