



Product overview

Vertiface® is a durable, versatile wallcovering made from 100% polyester fibre. With a soft velour finish on one side, and sleek flat pile on the other, Vertiface can be used as a furnishing fabric, wallcovering, and acoustic panel overlay. Vertiface is hook-and-loop receptive and pinnable with a self-healing surface.

Sustainable material

- Carbon neutral product
- Zero carbon manufacturing
- Recycled content - >80% recycled material
- Low VOC and CDPH compliant - <0.0035 mg/m³ (7 days)
- Zero waste manufacturing initiative
- Sustainable supply chain and anti-modern slavery

Environmental certifications

- EPD – compliant with ISO 14025 and ISO 15804
- Declare – Red List free (third party verified)
- ISO 14001 Certified Environmental Management
- Health Product Declaration
- CDPH Standard



Certifying your green building

Autex Acoustics products meet criteria for WELL, LEED, Green Star, and BREEAM building rating systems, helping you achieve certification for your project. For support and guidance on available rating system points please visit www.autexglobal.com, or speak with your Autex Acoustics account manager.

Specification

(Wall) treatment shall be Vertiface® made from non-woven needle-punched polyester containing no less than 80% recycled material as manufactured by Autex www.autexglobal.com

Roll 3 - 4 mm (nom.) depth, colour (), Fire Rating ISO 9705: Classification: Group 1-S, AS ISO 9705 – 2003 Classification: Group 1, EN13501-1:2007+A1:2009: B - s1, d2

Product specifications

Product name Vertiface®
Composition 100% polyester fibre (PET)
Roll dimensions 1.3 m x 50 m
Tolerance (+ 5 mm) x (+ 10 mm)
Thickness (nom.) 3 - 4 mm
Weight Typically 380 gsm
 Other widths are available on request, MOQ's apply.

Installation
 Install as per Autex Acoustics recommendations. Install instructions are included in each pack or available on the website.

If Vertiface is to be specified for use other than as a wallcovering, please seek guidance from your account manager.



Product specifications

Fire ratings

Vertiface has been evaluated using the following test methods

ISO 9705: 1993

Classification: Group 1-S

Smoke production rate:

<5.0m²/s

As required by NZBC C/VM2

AS ISO 9705 - 2003

Classification: Group 1

(SMOGR_{ARC}): <100m²/s²

Assessed using methodology AS ISO 9705:2003

in accordance with AS 56371:2015, as required by

BCA Specification C110-4

FI 4906

FAR 4055

BS EN 13501-1:2018

Classification: B-s1,d0

Tested using BS EN ISO 11925-2:2020 and BS EN

13823:2020 and classified in accordance with BS

EN 13501-1:2018, as required by BS EN 15102:2007

+ A1:2011.

EUI-21-000135-C

ASTM E84 - 01

Class A, FS:20 - SD:50

01.04913.01.206a

Water vapour sorption

ASTM C1104 / C1104M-13a

Test conditions: 49°C, 95%RH

Water vapour absorbed and

adsorped after

4 days: 0.4% by weight

Microbial resistance

ASTM G21-15

Growth rating: 0 (No growth)

Vertiface does not promote the

growth of moulds and mildew.

Colour fastness to light

Vertiface is suitable for indoor

use only. Light fastness

is dependent on use and

exposure. Vertiface has

been evaluated to the

following standard:

ISO 105-B02:2014

Rating: 6 (Highest = 7)

Colour fastness to rubbing

ISO 105-X12:2016

Dry rating: 4-5 (Highest = 5)

Wet rating: 4-5 (Highest = 5)

Pattern repeat

Non-woven. No pattern repeat

but product has directional

grain. Product may vary from

samples and batch to batch

due to fibre blending and

lay-up, which is an inherent

feature of this product.

Fabric care

Blot spills from fabric quickly.

Wipe with a damp cloth. Avoid

rubbing and excessive amounts

of water as this will affect the

finish. Use carpet or upholstery

shampoo as directed. Blot with

a clean dry cloth after each

application of solution.

Custom printed Vertiface requires the services of a specialist cleaning company. Refer to the Vertiface Care and Maintenance Guide for more information.

Service

For further information about Vertiface or any other Autex Acoustics product, please contact your account manager or visit our website.

Light reflectance values by colour

Vertiface LRVs were measured in accordance with BS 8493:2008+A1:2010

Civic	57	Koala	12
Citrus	49	Avocado	11
Myst	42	Sage	9
Sanz	36	Emerald	8
Wasabi	33	Sapphire	8
Lime	29	Atlantis	8
Azure	24	Blazing Red	8
Silver	23	Raspberry	8
Jade	22	Vintage	6
Porcelain	22	Chilli Red	5
Calypso	13	Cinder	5
Fawn	20	Bark	5
Clay	20	Octane	5
Granny Smith	20	Phantom	4
Stone wash	19	Theatre	3
Simba	18	Stately	3
Brilliant Orange	15	Charcoal	3
Spearmint	13	Lightsout	3
Calypso	13	Ink	3
Electric Blue	12	Noir	1

