

RP Series

Models	RP6502	RP7502	RP8602
Panel			
Screen Size	65"	75"	86"
Backlight / Lightsource	DLED	DLED	DLED
Resolution (Pixel)	UHD 3840 x 2160 pixels	UHD 3840 x 2160 pixels	UHD 3840 x 2160 pixels
Brightness (Typical)	350 nits	450 nits	400nits
Contrast Ratio (Typical)	1,200:1	1,200:1	1,200:1
View Angle (Horizontal / Vertical)	178°/178°	178°/178°	178°/178°
Response Time (ms)	8ms	8ms	8ms
Color Gamut (x% NTSC)	68%	72%	68%
Light Life (Typical)	30,000 hours	30,000 hours	30,000 hours
Display Orientation	Landscape	Landscape	Landscape
Glass			
Tempered Glass	4mm Tempered Glass	4mm Tempered Glass	4mm Tempered Glass
Anti-Glare & Germ-Resistant Screen	Yes	Yes	Yes
Touch			
Touch Technology	IR	IR	IR
Numbers of Touch	Up to 20 points Multi-touch	Up to 20 points Multi-touch	Up to 20 points Multi-touch
Touch interface	USB B Touch Port x3	USB B Touch Port x3	USB B Touch Port x3
Connectivity & Sensor			
Connector	VGA x1, HDMI 2.0 x3, HDMI Out x1, 3.5mm Audio Line in/Mic in x1, 3.5mm Audio Line out x1, SPDIF Audio out x1, USB 2.0 x3, USB 3.0 x2, USB B Touch Port x3, Type C x1, RS232 x1, RJ45 x1, OPS Slot x1	VGA x1, HDMI 2.0 x3, HDMI Out x1, 3.5mm Audio Line in/Mic in x1, 3.5mm Audio Line out x1, SPDIF Audio out x1, USB 2.0 x3, USB 3.0 x2, USB B Touch Port x3, Type C x1, RS232 x1, RJ45 x1, OPS Slot x1	VGA x1, HDMI 2.0 x3, HDMI Out x1, 3.5mm Audio Line in/Mic in x1, 3.5mm Audio Line out x1, SPDIF Audio out x1, USB 2.0 x3, USB 3.0 x2, USB B Touch Port x3, Type C x1, RS232 x1, RJ45 x1, OPS Slot x1
Built-in Camera	No	No	No
Built-in Microphone	Array Microphone x8	Array Microphone x8	Array Microphone x8
Built-in speaker	Speakers 16W x2 & Subwoofer 15W x1	Speakers 16W x2 & Subwoofer 15W x1	Speakers 16W x2 & Subwoofer 15W x1
Sensor	NFC Sensor x1, Motion Sensor (PIR) x3, Air Quality Sensor x1, Light Sensor x1,	NFC Sensor x1, Motion Sensor (PIR) x3, Air Quality Sensor x1, Light Sensor x1,	NFC Sensor x1, Motion Sensor (PIR) x3, Air Quality Sensor x1, Light Sensor x1,
Power			
Voltage	AC 100-240V~ 50/60Hz	AC 100-240V~ 50/60Hz	AC 100-240V~ 50/60Hz
Typical (Watt)	141.5W	262.4W	296.2W
Mechanical			
Weight	44 kg	61 kg	79 kg
Dimension (WxHxD) (mm)	1505.9 x 951.0 x 121.5	1735.5 x 1085.8 x 130.7	1988.8 x 1229.8 x 138.4
Wall Mounting (VESA) (mm)	4 holes (600 x 400mm) Screw M8 x 20mm	4 holes (600 x 400mm) Screw M8 x 20mm	4 holes (600 x 400mm) Screw M8 x 20mm
Handle	x2	x2	x4
OSD			
On-Screen Display Languages	English / French / German / Dutch / Polish / Russian / Czech / Danish / Swedish / Italian / Romanian / Finnish / Norwegian / Greek / Hungarian / Spanish / Portuguese / Traditional Chinese / Simplified / Chinese / Arabic / Japanese / Thai / Persian / Vietnamese / Korea / Turkey / indonesia (27L)	English / French / German / Dutch / Polish / Russian / Czech / Danish / Swedish / Italian / Romanian / Finnish / Norwegian / Greek / Hungarian / Spanish / Portuguese / Traditional Chinese / Simplified / Chinese / Arabic / Japanese / Thai / Persian / Vietnamese / Korea / Turkey / indonesia (27L)	English / French / German / Dutch / Polish / Russian / Czech / Danish / Swedish / Italian / Romanian / Finnish / Norwegian / Greek / Hungarian / Spanish / Portuguese / Traditional Chinese / Simplified / Chinese / Arabic / Japanese / Thai / Persian / Vietnamese / Korea / Turkey / indonesia (27L)
Package / Accessory			
Remote Controller	x1	x1	x1
Power Cord	By Region	By Region	By Region
Cable	VGA x1, HDMI x1, USB for touch x1, TYPE-C x1	VGA x1, HDMI x1, USB for touch x1, TYPE-C x1	VGA x1, HDMI x1, USB for touch x1, TYPE-C x1
Quick Start Guide	x1	x1	x1
User's Manual Electronic File	x1	x1	x1
Touch Pen	x2	x2	x2
Wall Mount	x1	x1	x1
Optional			
Accessory User manual	InstaShow, WiFi Dongle, OPS, Trolley	InstaShow, WiFi Dongle, OPS, Trolley	InstaShow, WiFi Dongle, OPS, Trolley