Revision Date: Monday, 21 February 2022

EchoPanel® Empire

Designer: Woven Image

Application(s): Walls, Partitions

Composition & Pattern

Composition 100% PET (60% post-consumer recycled)

Colours Available 33

Pattern Type Precision Cut

Dimensions & Weight

Dimensions Length: 2750mm (+/-2 mm), Width: 1100mm (+/-2mm), Thickness:

12mm (+/- 7%). Also available in 24mm (+/-7%), specifications will

differ.

Unit of Sale Panel

Unit of Sale Net Weight (kg) 8

Performance

Fire Test Result AS 1530.3, BS EN 13501.1: Classification B - s1, d0, GB 8624 B1, ISO

9705: Group 1, BS EN 45545-2 + A1 Annex C: CIT: 0.05

Acoustic Performance Standard Test AS ISO 354: 2006 (R2016), AS ISO 11654: 2002 (2016), ASTM C423 - 17

Method

Noise Reduction Coefficient (NRC) Direct fix: 0.45, 20mm air gap: 0.60, 50mm air gap: 0.75

Result

Direct fix: 0.43, 20mm air gap: 0.61, 50mm air gap: 0.75 Sound Absorption Average (SAA)

Result

Direct fix: 0.30 (MH), 20mm air gap: 0.45 (MH), 50mm air gap: 0.60 **Weighted Sound Absorption**

Coefficient (aw) Result

D (Direct fix), D (20mm air gap), C (50mm air gap) **Sound Absorption Class**

Additional Acoustic Information Noise reduction coefficient result key: H = High Frequency / MH =

Mid to High Frequency

Colour Fastness to Light Standard

Test Method

ISO 105 B02

Colour Fastness Light Rating 6 - 7

Sustainability

ASTM D5116: TVOC Emissions Rate: <0.02mg/m²/hr (7 days), and **VOC Emissions Results**

CDPH Standard Method v1.2: TVOC Emissions Rate: <0.054mg/m³;

Formaldehyde Emissions Rate: <2µg/m³

Sustainability Performance













Instructions

Product Care Instructions See Woven Image EchoPanel Care & Cleaning Guide

See Woven Image EchoPanel Precision Cut Panels Installation

Guide

